






Nominal power	kW	7
Reduced power	kW	2,6
Introduced thermal power (max)	kW	7,7
Nominal water useful power	kW	-
Reduced water useful power	kW	-
Nominal efficiency	%	90
Reduced efficiency	%	92
Heating volume (min-max)	m ³	62 - 168
Nominal CO at 13% O ₂	%	0,0034
Reduced CO at 13% O ₂	%	0,0127
Emissions CO (13% O ₂) (min-max)	mg/Nm ³	158 - 42
Emissions OGC (13% O ₂) (min-max)	mg/Nm ³	2,0 - 1,0
Emissions NOX (13% O ₂) (min-max)	mg/Nm ³	137 - 117
Dust content at 13% O ₂ (min-max)	mg/Nm ³	18 - 15
Boiler capacity (H ₂ O)	l	-
Hopper capacity	kg	15
Combustible		Pellet ø6
Hourly consumption (min-max)	kg/h	0,56 - 1,65
Autonomy (min-max)	h	9,1 - 26,8
Ignition electrical absorption (max)	W	345
Operating electrical absorption (max)	W	49
Supply and frequency	V - Hz	230 - 50
Chimney flue depression	Pa	10
Exhaust diameter	mm	80
Combustion air inlet diameter	mm	60
Mass of smoke (min-max)	g/sec	3 - 4,6
Exhaust fumes temperature (max)	°C	176
Net weight	kg	56
Gross weight	kg	66
Exhaust fumes	see	A
Hole combustion air inlet	see	B
Ducting outlet	see	-
Ducting capability up to	m	-




MATCH

7020026	NEUTRAL STRUCTURE	EAN 8053859012429
6920024	Anthracite steel	EAN 8053859012436
6920025	White steel	EAN 8053859012443
6920026	Red steel	EAN 8053859012450

PLUS

- Sealed chamber
- Cast iron burning pot
- Connection to the room thermostat
- Daily weekly programming
- Back exhaust
- Remote control
- Wi-fi optional
- Comfort mode
- Shield


STOVE PACKING



L (cm)	H (cm)	P (cm)
80	114,3	60


VOLUME (m ³)
0,55

LINING PACKING



L (cm)	H (cm)	P (cm)	
Steel	48,5	8	94,5

STOCKING



TRANSPORT

